

# Laundry Press – Air operated collar and cuff

## FPA6-WC



### Features and benefits

- High temperature polished head, dries the fabric and gives it a flat finish
- High pressure, achieves an excellent finish
- Adjustable pressure regulator, for pressing different fabrics
- Air operated, reduces operator fatigue
- Safety two button closing, improves operator safety
- Padded buck, reduces impressions
- Adjustable release timer, simplifies the operation and ensures consistent results

### Main options

- Facilities that simplify the installation
  - Integral air compressor
  - Integral steam boiler

Electrical connections		Standard	Built-in boiler	Built-in air comp.
Voltage, external boiler 208-240V 1 AC 50/60 Hz	kW	0.2		1.1
Voltage, internal boiler 208-240V 3 AC 50/60 Hz	kW	-	alt 8.4	-
400-415V 3N AC 50/60 Hz	kW	-	10.4	-
		-	12.4	-
		-	15.4	-
		-	18.4	-
Steam, air and vacuum connection				
Steam	DN	15	-	15
Rec. steam pressure	kPa	600	-	600
Steam consumption	kg/h	12-13	-	12-13
Condensate	DN	15	15	15
Compressed air	DN	10	10	-
Rec. air pressure	kPa	700	700	-
Air consumption	l/min	50	50	50
Boiler drain (internal boiler)	DN	-	15	-
Shipping data				
	net, kg	300	300	300
	crated, kg	360	360	360
	boxed, kg	440	440	440
Dimensions in mm				
<b>A</b> Width		970	970	970
<b>B</b> Depth		1135	1135	1135
<b>C</b> Height		1220	1220	1220
<b>D</b>		1530	1530	1530
<b>E</b>		1070	1070	1070
<b>F</b>		780	780	780
<b>G</b>		445	445	445
<b>H</b>		190	190	190
<b>I</b>		150	150	150
<b>K</b>		505	505	505
<b>L</b>		300	300	300
<b>1</b> Control panel	<b>5</b> Air connection			
<b>2</b> Electrical connection	<b>6</b> Boiler drain (internal boiler)			
<b>3</b> Steam connection	<b>7</b> Water supply (internal boiler)			
<b>4</b> Condensate				

