

Steam Boilers

FSB18C, FSB24C



Features and benefits

- Range of capacity from 8-25kg and 8-32kg steam/hour
- Free standing package boiler
- Standard with integral water feed pump
- Water feed/condensate tanks for energy efficiency/simple installation
- Variable heating control for energy saving when full capacity is not required
- Stainless steel tank for condensate recovery and energy efficiency
- Moving parts reduced to a minimum for low maintenance cost
- Economizer to reduce water and energy consumption (option)

Electrical connections		FSB18C	FSB24C
Voltage	400V 3N AC 50Hz kW(A)	19(32)	25(40)
Boiler heating			
Steam output	kg/h	25	32
Rating	kW	18	24
Steam outlet, drain, water connections			
Steam outlet	DN	15	15
Max. steam pressure	kPa	500	500
Water supply	mm	16	16
Condensate inlet	DN	12	12
Boiler drain	DN	15	15
Shipping data			
Weight	net, kg	110	110
	crated, kg	140	140
Dimensions in mm			
A	Width	460	460
B	Depth	810	810
C	Height	1178	1178
D		767	767
E		701	701
F		451	451
G		94	94
H		127	127
1	Control panel	4	Condensate inlet
2	Electrical connection	5	Water supply
3	Steam outlet	6	Boiler drain

